



FortiGate/FortiWiFi® 60D Series

Integrated Threat Management for Small Networks



FortiGate/FortiWiFi® 60D Series

Integrated Threat Management for Small Networks

The FortiGate/FortiWiFi 60D Series are compact, all-in-one security appliances that deliver Fortinet's Connected UTM. Ideal for small business, remote, customer premise equipment (CPE) and retail networks, these appliances offer the network security, connectivity and performance you need at a single low per-device price.

Consolidated Security Solutions

You get advanced threat protection, including firewall, application control, advanced threat protection, IPS, VPN, and web filtering, all from one device that's easy to deploy and manage. With our FortiGuard® security subscription services you'll have automated protection against today's sophisticated threats.

Reduce the need for additional wireless access points by integrating a high-bandwidth "fatclient" into your FortiGate with the FortiWiFi 60D. It's also a great option to secure mobile devices in BYOD environments with automatic device identification and customizable access and security policies.

VDOMs on the FortiGate/FortiWiFi 60D let you segment networks to enable guest and employee access, or protect things like cardholder data. You get the flexibility to match your business needs and meet compliance standards like PCI and HIPAA.

Key Features & Benefits

| Unified Security | Multi-threat protection from a single device increases security and lowers costs |
|-----------------------|--|
| Simplified Licensing | Unlimited user licensing and comprehensive features |
| Multi-Port Interfaces | Multiple network interfaces and optional wireless connectivity enable data segmentation for compliance and flexible deployment |

Enterprise-Class Protection that's Easy to Deploy and Manage

- 1.5 Gbps throughput performance ensures your network security won't be a bottleneck
- Integrated switch and options for PoE simplify your network infrastructure
- Up to 2x WAN, 7x LAN and 1x DMZ interface ports (2x Power over Ethernet ports on PoE models)
- Runs on FortiOS 5 the most powerful security operating system in the world delivers more security to fight advanced threats, more control to secure mobile devices, and more intelligence to build secure policies


















DATA SHEET: FortiGate/FortiWiFi® 60D Series

HARDWARE

FortiGate 60D





Interfaces

- 1. Console Port
- 2. USB Management Port for FortiExplorer
- 3. USB Port
- 4. 2x GE RJ45 WAN Ports
- 5. 1x GE RJ45 DMZ Ports
- 6. 7x GE RJ45 Internal Ports / 5x GE RJ45 Internal and 2x GE PoE Ports on POE models



Powered by FortiASIC SoC2

- Combines a RISC-based CPU with Fortinet's proprietary FortiASIC™ content and network processors for unmatched performance
- Simplifies appliance design and enables breakthrough performance for smaller networks
- Supports firewall acceleration across all packet sizes for maximum throughput
- Delivers accelerated UTM content processing for superior performance and protection
- Accelerates VPN performance for high speed, secure remote access

FortiWiFi 60D





FortiGate 60D-POE





FortiWiFi 60D-POE





Install in Minutes with FortiExplorer

The FortiExplorer™ wizard enables you to easily and quickly set up and configure FortiGate and FortiWiFi platforms with easy-to-follow instructions. The application runs on Windows, Mac OS X desktops and laptops as well as popular mobile devices. Simply connect to the appropriate USB port on the appliance, and be fully protected in minutes.

3G/4G WAN Connectivity

The FortiGate/FortiWiFi 60D Series includes a USB port that allows you to plug in a compatible third-party 3G/4G USB modem, providing additional WAN connectivity or a redundant link for maximum reliability.

Compact and Reliable Form Factor

Designed for small environments, you can place it on a desktop or wall-mount it. It is small, lightweight yet highly reliable with superior MTBF (Mean Time Between Failure), minimizing the chance of a network disruption.

Superior Wireless Coverage

A built-in dual-band, dual-stream access point with internal antennas is integrated on the FortiWiFi 60D and provides speedy 802.11n coverage on both 2.4 GHz and 5 GHz bands. The dualband chipset addresses the PCI-DSS compliance requirement for rogue AP wireless scanning, providing maximum protection for regulated environments.

www.fortinet.com



FortiOS — The World's Most Advanced Security Operating System

Feature Select

Instantly fine-tunes the FortiGate based on desired deployment needs using feature presets. Simplifies user administration and configurations while providing flexibility for different deployment modes.

Contextual Visibility

Presents critical deep insights into historic or real-time network activities with data on threat details, IPs, users, devices, applications and more. Allows administrators to quickly understand threats and stop them.

Advanced Security

Multiple advanced technologies can be coordinated to look for and stop today's blended, targeted or unknown attacks. Efficient packet handling improves performance while lowering latencies and reducing network complexities.

For complete, up-to-date and detailed feature set, please refer to the Administration Handbook and FortiOS Datasheet

Industry Validation

The FortiGate family of physical and virtual appliances has earned more certifications than any other vendor by consistently meeting rigorous third-party standards. Our industry-leading technology provides you with air-tight security which you can safely count on.

More Protection and Better ROI

The FortiGate constantly evolves itself in its mission to provide more value for users. Extended features such as WiFi controller, integrated token server, endpoint control and WAN optimization add more security to organizations without incurring additional cost.

Complete and Real-time Security

Fortinet FortiGuard Subscription Services provide automated, real-time, up-to-date protection against the latest security threats. Our threat research labs are located worldwide, providing 24x7 updates when you most need it.

World-Class Technical Support and Documentation

Fortinet FortiCare support offerings provide comprehensive global support for all Fortinet products and services. You can rest assured your Fortinet security products are performing optimally and protecting your users, applications, and data around the clock.



 $\label{eq:continuous} \textbf{FortiOS Dashboard} - \textbf{Single Pane of Glass Management}$

ORDER INFORMATION

| Product | SKU | Description |
|-------------------|-------------|---|
| FortiGate 60D | FG-60D | 10x GE RJ45 ports (including 7x Internal ports, 2x WAN ports, 1x DMZ port). Maximum managed FortiAPs (Total / Tunnel) 10 / 5. |
| FortiWiFi 60D | FWF-60D | 10x GE RJ45 ports (including 7x Internal ports, 2x WAN ports, 1x DMZ port), Wireless (802.11a/b/g/n). Maximum managed FortiAPs (Total / Tunnel) 10 / 5. |
| FortiGate 60D-P0E | FG-60D-POE | 10x GE RJ45 ports (including 5x Internal ports, 2x WAN ports, 1x DMZ port, 2x PoE ports). Maximum managed FortiAPs (Total / Tunnel) 10 / 5. |
| FortiWiFi 60D-P0E | FWF-60D-POE | 10x GE RJ45 ports (including 5x Internal ports, 2x WAN ports, 1x DMZ port, 2x PoE ports), Wireless (802.11a/b/g/n). Maximum managed FortiAPs (Total / Tunnel) 10 / 5. |

SPECIFICATIONS

| | FORTIGATE 60D | FORTIWIFI 60D | FORTIGATE 60D-POE | FORTIWIFI 60D-POE | | |
|--|---|-------------------------------|-------------------------------|-----------------------------|--|--|
| Hardware Specifications | | | | | | |
| GE RJ45 WAN Ports | 2 | 2 | 2 | 2 | | |
| GE RJ45 Internal Ports | 7 | 7 | 5 | 5 | | |
| GE RJ45 PoE Ports | _ | _ | 2 | 2 | | |
| GE RJ45 DMZ Ports | 1 | 1 | 1 | 1 | | |
| Nireless Interface | _ | 802.11 a/b/g/n | _ | 802.11 a/b/g/n | | |
| JSB Ports (Client / Server) | 1/1 | 1/1 | 1/1 | 1/1 | | |
| Console (RJ45) | 1 | 1 | 1 | 1 | | |
| System Performance | | | | | | |
| Firewall Throughput (1518 / 512 / 64 byte UDP packets) | | 1.5 / 1.5 | 5 / 1.5 Gbps | | | |
| Firewall Latency (64 byte UDP packets) | 4 µs | | | | | |
| Firewall Throughput (Packets Per Second) | 2.2 Mpps | | | | | |
| Concurrent Sessions (TCP) | 500,000 | | | | | |
| New Sessions/Sec (TCP) | 4,000 | | | | | |
| Firewall Policies | 5,000 | | | | | |
| Psec VPN Throughput (512 byte packets) | | | | | | |
| Gateway-to-Gateway IPsec VPN Tunnels | 200 | | | | | |
| Client-to-Gateway IPsec VPN Tunnels | 500 | | | | | |
| SSL-VPN Throughput | 30 Mbps | | | | | |
| Concurrent SSL-VPN Users (Recommended Maximum) | 30 Waps | | | | | |
| PS Throughput | | | | | | |
| CAPWAP Clear-text Throughput (HTTP) | 200 Mbps 175 Mbps | | | | | |
| Antivirus Throughput (Proxy Based / Flow Based) | 35 / 50 Mbps | | | | | |
| /irtual Domains (Default / Maximum) | 10 / 10 | | | | | |
| Maximum Number of FortiAPs (Total / Tunnel Mode) | 10/5 | | | | | |
| Maximum Number of FortiTokens | 107 3 | | | | | |
| Maximum Number of Registered FortiClients | | | 200 | | | |
| High Availability Configurations | Active / Active / Passive, Clustering | | | | | |
| Dimensions | | | , | | | |
| Height x Width x Length (inches) | 1.50 x 8.50 x 5.83 | 1.50 x 8.50 x 6.18 | 1.50 x 8.50 x 5.83 | 1.50 x 8.50 x 6.18 | | |
| Height x Width x Length (mm) | 38 x 216 x 148 | 38 x 216 x 157 | 38 x 216 x 148 | 38 x 216 x 157 | | |
| Weight | 1.9 lbs (0.9 kg) | 1.9 lbs (0.9 kg) | 1.9 lbs (0.9 kg) | 1.9 lbs (0.9 kg) | | |
| Form Factor | Desktop | Desktop | Desktop | Desktop | | |
| Environment | υσοπορ | Σουπορ | Dourtoh | Σουπορ | | |
| | 400 040140 50 0011 | | | | | |
| Power Required | 100–240V AC, 50–60 Hz | | | | | |
| Maximum Current Total Available Dec Dower Budget* | 110 V / 1.5 A, 220 V / 0.75 A | 110 V / 1.5 A, 220 V / 0.75 A | 110 V / 1.5 A, 220 V / 0.75 A | 110 V / 1.5 A, 220 V / 0.75 | | |
| Total Available PoE Power Budget* | 11 7 / 14 \\\ | 11 7 / 14 \\\ | 30.8 W | 30.8 W | | |
| Power Consumption (Average / Maximum) | 11.7 / 14 W | 11.7 / 14 W | 27.4 / 45.2 W | 29.9 / 48.2 W | | |
| Heat Dissipation | 40 BTU/h | 40 BTU/h | 154 BTU/h | 165 BTU/h | | |
| Operating Temperature | 32–104°F (0–40°C) | | | | | |
| Storage Temperature | | | F (-35–70°C) | | | |
| Humidity | 20–90% non-condensing | | | | | |
| Operating Altitude | Up to 7,400 ft (2,250 m) | | | | | |
| Compliance | | | | | | |
| Safety | FCC Part 15 Class B, C-Tick, VCCI, CE, UL/cUL, CB | | | | | |
| outoty | | | | | | |

Note: All performance values are "up to" and vary depending on system configuration. Antivirus performance is measured using 44 Kbyte HTTP files. IPS performance is measured using 1 Mbyte HTTP files.

^{*} Maximum loading on each PoE port is 15.4 W (802.3af).



FST-PROD-DS-GT60D

GLOBAL HEADQUARTERS Fortinet Inc. 899 Kifer Road Sunnyvale, CA 94086 United States Tel: +1.408.235.7700 www.fortinet.com/sales

EMEA SALES OFFICE 120 rue Albert Caquot 06560, Sophia Antipolis, France Tel: +33.4.8987.0510

APAC SALES OFFICE 300 Beach Road 20-01 The Concourse Singapore 199555 Tel: +65.6513.3730

LATIN AMERICA SALES OFFICE Prol. Paseo de la Reforma 115 Int. 702 Col. Lomas de Santa Fe, C.P. 01219 Del. Alvaro Obregón México D.F. Tel: 011-52-(55) 5524-8480

Copyright® 2015 Fortinet, Inc. All rights reserved. Forticate®, Forticate®, Forticate® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., in the U.S. and other jurisdictions, and actual performance and other results may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other merics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect the product results may vary. Network variables, different networks environments and other conditions may affect the product variables. The product of the product results may vary. Network variables, different networks environment to produce and other results may vary. Network variables, different networks environment to produce and other results may vary. Network variables, different networks environment to produce the variables, different networks environment to produce the variables. The product of the product variables and the product variables and the product variables. The product variables are produced to produce the variables and the product variables. The variables are produced to produce the variables and the variables. The variables are produced to produce the variables and the variables. The variables are produced to produce the variables and the variables. The variables are produced to produce the variables and the variables. The variables are produced to produce the variables and the variables. The variables are produced to produce the variables and the variables. The variables are produced to produce the variables are produced to produce the variables. The variables are produced to produce the variables are produced to produce the variables. The variables are produced to produce the variables are produced to produce the variables are produced to produce the variables. The