



# EMC DATA DOMAIN DEDUPLICATION STORAGE SYSTEMS

EMC Data Domain deduplication storage systems continue to revolutionize disk backup, archiving, and disaster recovery with high-speed, inline deduplication. By consolidating backup and archive data on a Data Domain system, you can reduce storage requirements by 10-30x, making disk cost-effective for onsite retention and highly efficient for network-based replication to disaster recovery sites.

## Specifications

### DATA DOMAIN CONTROLLER PERFORMANCE AND CAPACITY

	DD2200	DD2500	DD4200	DD4500	DD7200	DD9500
<b>MAXIMUM THROUGHPUT (OTHER)</b>	3.8 TB/hr	5.6 TB/hr	10.6 TB/hr	10.6 TB/hr	12.6 TB/hr	27.7 TB/hr
<b>MAXIMUM THROUGHPUT (DD BOOST)</b>	4.7 TB/hr	13.4 TB/hr	25.6 TB/hr	25.6 TB/hr	28.3 TB/hr	58.7 TB/hr
<b>LOGICAL CAPACITY<sup>1</sup></b>	40-860 TB	1.3-6.6 PB	1.8-9.4 PB	2.8-14.2 PB	4.2-21.4 PB	8.6-43.2 PB
<b>LOGICAL CAPACITY W/ DD EXTENDED</b>			3.7 - 18.9 PB	5.7 - 28.5 PB	8.5 - 42.8 PB	17.2-86.4 PB
<b>MAX USABLE</b>	Up to 17.2 TB	Up to 133 TB	Up to 189 TB	Up to 285 TB	Up to 428 TB	Up to 864 TB
<b>MAX USABLE CAPACITY W/ DD EXTENDED</b>			Up to 378 TB	Up to 570 TB	Up to 856 TB	Up to 1.7PB
<b>ES30 SHELVES</b>	-	2 TB, 3 TB	2 TB, 3 TB	2 TB, 3 TB, 4TB <sup>2</sup>	2 TB, 3 TB, 4TB <sup>2</sup>	2 TB, 3 TB, 4TB <sup>2</sup>
<b>DRIVE TYPE</b>	SAS	SAS	SAS, SATA	SAS, SATA	SAS, SATA	SAS, SATA
<b>DS60 SHELF</b>	N/A	N/A	3 TB	3 TB, 4 TB <sup>2</sup>	3 TB, 4 TB <sup>2</sup>	3 TB, 4 TB <sup>2</sup>
<b>DRIVE TYPE</b>	N/A	N/A	SAS	SAS	SAS	SAS

1. Mix of typical enterprise backup data (file systems, databases, email, developer files). The low end of capacity range represents a full backup weekly or monthly, incremental backup daily or weekly, to system capacity. The top end of the range represents full backup daily, to system capacity. All capacity values are calculated using Base10 (i.e., 1TB = 1,000,000,000,000 bytes).

2. No SATA Drive for 4TB drives

	<b>DD2200</b>	<b>DD2500</b>	<b>DD4200</b>	<b>DD4500</b>	<b>DD7200</b>	<b>DD9500</b>
<b>BUILT-IN NETWORKING</b>	1x Mgm't port 4x 1Gbe	1x Mgm't port 4x 1Gbe, 2x 10Gbe	1x Mgm't Port	1x Mgm't port	1x Mgm't port	1x Mgm't port 4x 1Gbe
<b>OPTIONAL NETWORKING W/ IO CARDS</b>	Up to 8x 1GbE	Up to 12x 1GbE	Up to 16x 1GbE	Up to 16x 1GbE	Up to 16x 1GbE	Up to 16X 1GbE
	Up to 4x 10GbE	Up to 6x 10GbE	Up to 8X 10GbE	Up to 8X 10GbE	Up to 8X 10GbE	
	Up to 8x 10GBase-T	Up to 12x 10GBaseT	Up to 16 10Gbase-T	Up to 16 10Gbase-T	Up to 16 10Gbase-T	Up to 8X 16Gb FC
	Up to 4X 8GB FC	Up to 6x 8Gb FC	Up to 8X 8Gb FC	Up to 8X 8Gb FC	Up to 6X 8Gb FC	

## DATA DOMAIN CONTROLLER PHYSICAL SPECIFICATIONS AND ENVIRONMENTALS

	<b>DD2200</b>	<b>DD2500</b>	<b>DD4200, DD4500, DD7200</b>	<b>DD9500</b>
<b>WEIGHT</b>	7 HDDs: 65 lbs 12 HDDs: 73 lbs	7 HDDs: 57 lbs 12 HDDs: 65 lbs	80 lbs	117 lbs
<b>DIMENSIONS</b>	19" x 29" x 3.5" 2U EIA rack units		19" x 35.5" x 7" 4U EIA rack units	19" x 27.7" x 6.8" 4U EIA rack units
<b>POWER</b> 100-120/200-240V~, 50/60 Hz	7 HDDs: 406 VA 12 HDDs: 502 VA	7 HDDs: 451 VA 12 HDDs: 526 VA	800 VA (200-240V Only)	1,887 VA (200-240 V Only)
<b>THERMAL RATING (WATTS)</b>	7 HDDs: 394 Watts 12HDDs: 487 Watts	7 HDDs: 428 Watts 12HDDs: 500 Watts	760 Watts	1,793 Watts
<b>THERMAL RATING (BTU/HR)</b>	7 HDDs: 1,344 BTU/hr 12HDDs: 1,662 BTU/hr	7 HDDs: 1,462 12HDDs: 1,705	2,593 BTU/hr	6,118 BTU/hr
<b>OPERATING TEMPERATURE/ ALTITUDE<sup>3</sup></b>	10°C to 35°C, 35°C at 7,500 ft			5°C to 35°C, 35°C at 7,500 ft
<b>NON-OPERATING (TRANSPORTATION) TEMPERATURE</b>	-40°C to +65°C (-40°F to +149°F)			
<b>OPERATING HUMIDITY</b>	20% to 80% non-condensing			
<b>OPERATION ACOUSTIC NOISE (SOUND POWER)</b>	LWAd: 7.52 bels		LWAd: 7.2 bels	
<b>OPERATION ACOUSTIC NOISE (SOUND PRESSURE)</b>	LpAm: 65 db	LpAm: 58.4 db	LpAm: 56.4 db	

3. Derate 1.1°C/1,000 ft above 7,500 ft to 10,000 ft

## DATA DOMAIN CONTROLLER REGULATORY APPROVALS

	<b>DD2200</b>	<b>DD2500</b>	<b>DD4200</b>	<b>DD4500</b>	<b>DD7200</b>	<b>DD9500</b>
<b>SAFETY</b>	UL 60950-1, CSA 60950-1, EN 60950-1, IEC 60950-1, GS, SABS, GOST, IRAM					
<b>EMISSIONS</b>	FCC Class A, EN 55022, CISPR 22, VCCI, BSMI, MIC, ICES-003					
<b>IMMUNITY</b>	EN 55024, CISPR 24					
<b>POWER LINE HARMONIS</b>	EN 61000-3-2					

## SOFTWARE

### SOFTWARE FEATURES

Global Compression™, Data Invulnerability Architecture including inline verification and integrated dual disk parity RAID 6, snapshots, telnet, FTP, SSH, email alerts, scheduled capacity reclamation, Ethernet failover and aggregation, Link Aggregation Control Protocol (LACP), VLAN tagging, IP aliasing, EMC Data Domain Boost, EMC Data Domain Encryption, EMC Data Domain Extended Retention (DD4200, DD4500, DD7200, DD9500 only), EMC Data Domain Replicator, EMC Data Domain Retention Lock optional software and EMC Data Domain Virtual Tape Library (for open systems and IBM i operating environments)

### SYSTEM MANAGEMENT

EMC Data Domain Management Center, EMC Data Domain System Manager, SNMP, and command line management interface

### DATA MANAGEMENT

NFS v3 over TCP, CIFS and DD Boost over 1 GbE or 10 GbE or Fibre Channel, tape library emulation (VTL) over Fibre Channel, and NDMP Tape Server

## DATA DOMAIN RACK

### POWER CONFIGURATION

Single phase is standard, optional 3-phase

Two power domains (base and extended), each redundant

### POWER INLET COUNT

Either two (for redundant base configuration) or four (for redundant extended configuration)

### PLUG TYPES

NEMA L6-30p or IEC 60309 332P6

### POWER CAPACITY

200-240 V~, single-phase, 47-63 Hz 4,800 VA (base configuration)

9,600 VA (extended configuration)

## **AC PROTECTION**

30 A site circuit breaker on each power domain

## **DIMENSIONS**

40U available rack capacity

Height: 75 in (190.8 cm); Width: 24.0 in (61.1 cm); Depth: 39.0 in (99.2 cm) Weight: 380 lbs (173 kg) when empty

## **ES30 EXPANSION SHELF**

### **EXTERNAL INTERFACE (HOST/EXPANSION)**

Dual 4 lane 6 Gb/s serial attached SCSI II (SAS) ports per Link Control Card (LCC)— one for host and one for expansion

### **CONNECTOR TYPE**

SFF-8088 connectors (mini-SAS)

### **SAS CABLE LENGTH**

Up to 5 meter

### **DISK DRIVES**

15-drive bays per ES30 expansion shelf, support low profile, one inch high, 3.5-inch form factor drives Drives Choices\*

SAS (6 Gb/s), 3 TB or 2 TB, & 7200 RPM

SATA (3 Gb/s), 3 TB or 2 TB or 1 TB, & 7200 RPM

Integrated SAS expander module for shelves with SATA drives Point-to-point disk connectivity

\* See Data Domain Controller Performance and Capacity section for Shelves & Drive Type Supported for each controller

## **DIMENSIONS**

Height: 5.25 in (13.34 cm)

Width: 19.0 in (48.3 cm)

Depth: 14.0 in (35.56 cm)

Weight: 68 lbs (30.8 kg)

## **OPERATIONAL**

Power (VA): 200-240 V~, 47 to 63 HZ

Thermal Rating: 800 BTU/hr, 235 Watts

Operating Temperature:

Ambient temperature: 41o F to 104o F (5o C to 40o C)

Temperature gradient: 18o F/hr (10o C/hr)

Relative humidity extremes: 20% to 80% noncondensing

Non-Operating (Transportation) Temperature:

Ambient temperature: -40o F to 149o F (-40o C to 65o F)

Temperature gradient: 45o F/hr (25oC/hr)

Relative humidity: 10% to 90% noncondensing

Elevation: -50 to 35,000 ft (-16 to 10,600 m)

## **DS60 EXPANSION SHELF**

### **EXTERNAL INTERFACE (HOST/EXPANSION)**

Quad 8 lane 12 Gb/s serial attached SCSI II (SAS) ports per Link Control Card (LCC)— Half of each port is blocked allowing the use of standard mini-SAS-HD connectors – one port is used for the host connection and the other is used for expansion. The host controller runs at 6Gb/s to the DS60

### **CONNECTOR TYPE**

SFF-8088 connectors (mini-SAS)

### **SAS CABLE LENGTH**

Up to 5 meter

### **DISK DRIVES**

60-drive bays per DS30 expansion shelf, support low profile, one inch high, 3.5-inch form factor drives Drives Choices\*

SAS (6 Gb/s), 3 TB & 4TB, 7200 RPM

Integrated SAS expander module for shelves with SATA drives Point-to-point disk connectivity

\* See Data Domain Controller Performance and Capacity section for Shelves & Drive Type Supported for each controller

### **DIMENSIONS**

Height: 8.75 in (22.23 cm) 5U (4U plus 1U cable management tray).

Width including rails: 17.50 in (44.45 cm)

Depth (chassis only): 34.5 in (87.63 cm)

Maximum depth (fully configured): 36.4 in (92.46 cm)

Weight: 225.0 lbs (90.7 kg) (with FRUs installed)

### **OPERATIONAL**

Power (VA): 200-240 V~, 47 to 63 HZ

Thermal Rating: 3177 BTU/hr

Operating Temperature:

Ambient temperature: 41o F to 104o F (5o C to 40o C)

Temperature gradient: 18o F/hr (10o C/hr)

Relative humidity extremes: 20% to 80% noncondensing

Elevation: -50 to 7500 ft (-16 to 2300 m)

Non-Operating (Transportation) Temperature:

Ambient temperature: -40o F to 149o F (-40o C to 65o F)

Temperature gradient: 45o F/hr (25oC/hr)

Relative humidity: 10% to 90% noncondensing

Elevation: -50 to 35,000 ft (-16 to 10,600 m)

## CONTACT US

To learn more about how EMC products, services, and solutions can help solve your business and IT challenges, [contact](#) your local representative or authorized reseller—or visit us at [www.EMC.com](http://www.EMC.com)

## CONFIGURE AND QUOTE

Visit the EMC Store



[store.emc.com/datadomain](http://store.emc.com/datadomain)

[www.EMC.com](http://www.EMC.com)

EMC<sup>2</sup>, EMC, the EMC logo, are registered trademarks or trademarks of EMC Corporation in the United States and other countries. VMware are registered trademarks or trademarks of VMware, Inc., in the United States and other jurisdictions. © Copyright 2015 EMC Corporation. All rights reserved. Published in the USA. 10/15 Specification Sheet H11340.1

EMC believes the information in this document is accurate as of its publication date. The information is subject to change without notice.