



APC Service Bypass Panel- 200/208/240V; 100A; MBB; Hardwire input; (6) L14-30R output

SBP16KRMP4U

Overview

Lead time Usually in Stock

Main

Main Input Voltage 208 V

Main Output Voltage 200 V
208 V

Other Output Voltage 240 V

Number of rack unit 4U

Provided Equipment Installation guide
Rack Mounting brackets
User Manual

Physical

Color Black

Height 7.01 in (17.8 cm)

Width 17.01 in (43.2 cm)

Depth 26.50 in (67.3 cm)

Net Weight 51.10 lb(US) (23.18 kg)

Mounting Location Front

Mounting preference Lower

Mounting Mode Rack-mounted

Input

Input Frequency 50/60 Hz

Number of input connectors 1 Hard Wire 3-wire (2PH + G)
1 Hard Wire 4-wire (2PH+N+G)

Max line current 100 A

Input current limits 100 A

Load Capacity 20000 VA

Load Power Factor Range 0...1

Output

Maximum Total Current Draw per Phase	100 A
Number of power socket outlets	6 NEMA L14-30R
Protection Type	Circuit breaker
Efficiency	99 %

Conformance

Product Certifications	CSA GOST
------------------------	-------------

Environmental

Ambient Air Temperature for Operation	-4...122 °F (-20...50 °C)
Relative Humidity	0...95 %
Operating altitude	0...15000 ft
Ambient Air Temperature for Storage	-40...149 °F (-40...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

GTIN	731304212669
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.01 in (30.5 cm)
Package 1 Width	39.02 in (99.1 cm)
Package 1 Length	24.02 in (61 cm)
Package 1 Weight	74.16 lb(US) (33.64 kg)

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	2 years (parts only)
----------	----------------------

Recommended replacement(s)