

Product data sheet

Specifications

APC Service Bypass Panel- 100-120V; 30A; BBM; L5-30P input; (2) 5-20R (6) 5-15R output



SBP3000RM2U



sales@corporatearmor.com
877.449.0458

Overview

Lead time Usually in Stock

Main

Main Input Voltage	100 V 120 V
Main Output Voltage	100 V 120 V
Other Output Voltage	110 V
Input Connection Type	NEMA L5-30P
Number of rack unit	2U
Cable length	10 ft (3.05 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets User Manual

Physical

Color	Black
Height	3.50 in (8.9 cm)
Width	17.01 in (43.2 cm)
Depth	25.51 in (64.8 cm)
Net Weight	30.07 lb(US) (13.64 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted

Input

Input Frequency	50/60 Hz
Max line current	24 A
Input current limits	24 A
Load Capacity	3000 VA
Load Power Factor Range	0...1

Output

Maximum Total Current Draw per Phase	30 A
Number of power socket outlets	6 NEMA 5-15R 2 NEMA 5-20R
Protection Type	Circuit breaker
Cord Length	10 ft (3.05 m)
Efficiency	99 %

Conformance

Product Certifications	CSA GOST
Standards	EN 60950 IEC 60950 IEC 60950 UL 1778

Environmental

Ambient Air Temperature for Operation	-4...122 °F (-20...50 °C)
Relative Humidity	0...95 %
Operating altitude	0...15000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

GTIN	731304212577
Package 1 Weight	54.15 lb(US) (24.56 kg)

Packing Units

Package 1 Height	7.99 in (20.3 cm)
Package 1 Width	24.02 in (61 cm)
Package 1 Length	39.02 in (99.1 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	2 years (parts only)
----------	----------------------