

Product data sheet

Specifications



sales@corporatearmor.com
877.449.0458

APC IT Power Distribution Module 3 Pole 5 Wire 30A L21-30 1040cm



PDM3530L2130-1040

Overview

Presentation Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.

Lead time Usually in Stock

Main

Main Input Voltage 3 phase

Main Output Voltage 120 V

Provided Equipment Installation guide

Physical

Color Black

Height 5.00 in (12.7 cm)

Width 17.52 in (44.5 cm)

Depth 15.98 in (40.6 cm)

Net Weight 9.46 lb(US) (4.29 kg)

Input

Input Frequency 60 Hz

Acceptable Input Voltage 200...240 V

Max line current 30 A

Output

Maximum Total Current Draw per Phase 30 A

Number of power socket outlets 1 NEMA L21-30

Conformance

Product Certifications UL Listed

Ordering and shipping details

GTIN 731304272380

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.00 in (12.7 cm)
Package 1 Width	15.98 in (40.6 cm)
Package 1 Length	17.52 in (44.5 cm)
Package 1 Weight	11.46 lb(US) (5.2 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Under investigation
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Take-back	Take-back program available

Recommended replacement(s)