



APC Surge Protection Module for RS232, Replaceable, 1U, for use with PRM4 or PRM24 Rackmount Chassis

P232R

Discontinued on: 21 September 2021

! Discontinued - Service only



sales@corporatearmor.com 877.449.0458

Overview

Lead time Usually in Stock

Main

Number of rack unit 0U

Provided equipment User Manual

Physical

Color	Black
Height	1.73 in (4.4 cm)
Width	0.75 in (1.9 cm)
Depth	2.72 in (6.9 cm)
Net Weight	0.40 lb(US) (0.18 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Output

Number of power socket outlets

Environmental

Ambient Air Temperature for Operation	23113 °F (-545 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	23113 °F (-545 °C)
Storage Relative Humidity	095 %
Storage altitude	010000 ft (0.003048.00 m)

Surge Protection and Filtering

Data Lines Protected(multi-line only)

1-8

NM Surge Response Time (ns)	1 ns common mode
Peak current	0.25 kA common mode 0.2 kA normal mode

Ordering and shipping details

GTIN	731304203384
Package 1 Weight	0.90 lb(US) (0.41 kg)

Packing Units

r acking office	
Package 1 Height	3.90 in (9.9 cm)
Package 1 Width	1.30 in (3.3 cm)
Package 1 Length	3.74 in (9.5 cm)
SCC14	30731304203385
Number of Units in Package 2	96
Package 2 Weight	13.67 lb(US) (6.20 kg)
Package 2 Height	8.125 in (206.38 mm)
Package 2 Width	16.25 in (412.75 mm)
Package 2 Length	25.125 in (638.18 mm)
Number of Units in Package 3	28

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	Take-back program available

Contractual warranty

Warranty Limited Lifetime