

Product data sheet

Specifications



Corporate Armor

sales@corporatearmor.com
877.449.0458



APC Replacement Battery Cartridge # 136 with 2 Year Warranty

APCRBC136

Product availability : Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Battery Type Lead-Acid battery

Provided Equipment Installation guide

Physical

Height 4.21 in (10.7 cm)

Width 4.21 in (10.7 cm)

Depth 5.67 in (14.4 cm)

Net Weight 7.28 lb(US) (3.3 kg)

Mounting Mode Not rack-mountable

Output

Battery Capacity 4.5 Ah

Environmental

Ambient Air Temperature for Operation 32...122 °F (0...50 °C)

Operating altitude 0...10000 ft

Relative Humidity 0...95 %

Ambient Air Temperature for Storage 5...113 °F (-15...45 °C)

Storage altitude 0...50000 ft (0.00...15240.00 m)

Storage Relative Humidity 0...95 %

Batteries & Runtime

Battery Placement Internal Battery

Battery blocks per string 2

Battery Slots Empty 0

Included Battery Modules 0

Device mounting	Stand alone battery stack
Battery Voltage	24 V
RBC Quantity	1

Ordering and shipping details

Category	09305-INDUSTRIAL UPS
Discount Schedule	IUPS
GTIN	731304293361
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

Packing Units

Package 1 Height	9.02 in (22.9 cm)
Package 1 width	9.02 in (22.9 cm)
Package 1 Length	9.02 in (22.9 cm)
Number of Units in Package 3	100

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------