

Product data sheet

Specifications

APC Smart-UPS Industrial Service Bypass Unit, 30A, 120V, rack mount, 2U, with generator input



XS30ALLXXR2G



Corporate Armor

sales@corporatearmor.com
877.449.0458

Overview

Lead time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	120 V
Main Output Voltage	110 V 120 V
Other Output Voltage	110 V
Output connector type	Hard Wire 3-wire (H N + E) 1
Number of rack unit	2U
Provided Equipment	Rack Mounting brackets

Physical

Color	Black
Height	3.45 in (8.76 cm)
Width	11.02 in (28 cm)
Depth	2.83 in (7.2 cm)
Net Weight	2.87 lb(US) (1.3 kg)
Mounting Support	Wall
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Input Frequency	50/60 Hz
Number of input connectors	1 Hard Wire 3-wire (1PH+N+G)
Max line current	30 A
Input current limits	30 A
Load Power Factor Range	0...1

Output

Maximum Total Current Draw per Phase	30 A
--------------------------------------	------

Protection Type	Circuit breaker
-----------------	-----------------

Efficiency	99 %
------------	------

Conformance

Product Certifications	CSA GOST VDE
------------------------	--------------------

Standards	EN 60950 IEC 60950 UL 1778
-----------	----------------------------------

Environmental

Ambient air temperature for operation	-35...165 °F (-37...74 °C)
---------------------------------------	----------------------------

Relative Humidity	0...95 %
-------------------	----------

Operating altitude	0...15000 ft
--------------------	--------------

Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
-------------------------------------	----------------------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0...50000 ft (0.00...15240.00 m)
------------------	----------------------------------

Ordering and shipping details

GTIN	731304399353
------	--------------

Package weight(Lbs)	4.50 lb(US) (2.04 kg)
---------------------	-----------------------

Packing Units

Package 1 Height	5.91 in (15 cm)
------------------	-----------------

Package 1 width	18.11 in (46 cm)
-----------------	------------------

Package 1 Length	11.61 in (29.5 cm)
------------------	--------------------

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------
