

Product data sheet

Specifications



APC Smart-UPS RT 48V Battery Pack

SURTA48XLBP



Corporate Armor

sales@corporatearmor.com
877.449.0458

Overview

Lead time Usually in Stock

Main

Number of rack unit 2U

Number of cables 1.0

Battery Type Lead-Acid battery

Provided Equipment Documentation CD
User Manual

Physical

Color Black

Height 17.80 in (45.2 cm)

Width 3.39 in (8.6 cm)

Depth 22.01 in (55.9 cm)

Net Weight 72.55 lb(US) (32.91 kg)

Mounting Mode Rack-mounted with kit

Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)

Operating altitude 0...10000 ft

Relative Humidity 0...95 % non-condensing

Ambient Air Temperature for Storage -4...122 °F (-20...50 °C)

Storage altitude 0...50000 ft (0.00...15240.00 m)

Storage Relative Humidity Non-condensing 0...95 %



Batteries & Runtime

Battery blocks per string 4

Battery Slots Empty 0

Included Battery Modules 2

Device mounting Enclosed battery cabinet

Battery Voltage	48V
RBC Quantity	2
Replacement battery	RBC57  SURTA48RMXLBP2U 

Ordering and shipping details

GTIN	731304226352
------	--------------

Packing Units

Unit Type of Package 1	PCE
Package 1 Length	24.02 in (61 cm)
Number of Units in Package 1	1
Number of Units in Package 3	12
Package 1 Width	28.74 in (73 cm)
Package 1 Height	10.00 in (25.4 cm)
Package 1 Weight	81.77 lb(US) (37.09 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------