

Product data sheet

Specifications



APC Smart-UPS X, Line Interactive, 3kVA, Rack/tower convertible 2U, 208V-230V, 8x C13+1x C19 IEC, SmartSlot, Extended runtime

SMX3000RMHV2U



Corporate Armor

sales@corporatearmor.com
877.449.0458

Overview

Presentation Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Lead time Usually in Stock

Main

Main Input Voltage	208 V 230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	208 V 220 V 240 V
Kw Rating	2700 W
Rated power in VA	3000 VA
Input Connection Type	IEC 320 C20 Schuko CEE 7 / EU1-16P BS1363A British
Output connection type	8 IEC 320 C13 2 IEC Jumpers 1 IEC 320 C19
Number of rack unit	2U
Cable length	6 ft (1.83 m)
Number of cables	1
Battery Type	Lead-Acid battery
Provided equipment	CD with software Documentation CD Smart UPS signalling RS-232 cable User Manual USB cable Rack Mounting brackets

General

Number of power module	2400
Number of power module filled slots	0
Number of power module free slots	0

Product web sub-family	Extended run
------------------------	--------------

Redundant	No
-----------	----

Physical

Color	Black
-------	-------

Height	3.35 in (8.5 cm)
--------	------------------

Width	17.01 in (43.2 cm)
-------	--------------------

Depth	26.26 in (66.7 cm)
-------	--------------------

Net Weight	82.28 lb(US) (37.32 kg)
------------	-------------------------

Mounting Location	Front
-------------------	-------

Mounting preference	Lower
---------------------	-------

Mounting Mode	Rack-mounted
---------------	--------------

Two post mountable	0
--------------------	---

USB compatible	Yes
----------------	-----

Input

Efficiency at full load	140...280 V
-------------------------	-------------

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
-----------------	--------------------------------

Output

Crest factor	3 : 1
--------------	-------

Harmonic distortion	Less than 5%
---------------------	--------------

Maximum configurable power in VA	3000 VA
----------------------------------	---------

Max Configurable Power (Watts)	2700 W
--------------------------------	--------

Transfer Time	2-4 ms 6ms typical : 10ms maximum
---------------	--------------------------------------

Topology	Line Interactive
----------	------------------

Waveform Type	Sine wave
---------------	-----------

Output frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

Conformance

Product Certifications	CE CSA EAC IRAM RCM VDE
------------------------	--

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Environmental

Acoustic level	55 dBA
----------------	--------

Heat dissipation	184 Btu/h
------------------	-----------





Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

Storage altitude	0...50000 ft (0.00...15240.00 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Batteries & Runtime

Extendable Run Time	1
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery Life	3...5 year(s)
Replacement battery	APCRBC117  APCRBC117US  SMX2KR2UX145  SMX3KR2UNCX145 
Battery power in VAH	738 VAh runtime
Battery Charge Power (Watts)	245 W rated
Battery option	SMX120RMBP2U 1 2214 VAh SMX120RMBP2U 2 3690 VAh SMX120RMBP2U 3 5166 VAh SMX120RMBP2U 4 6642 VAh SMX120RMBP2U 6 9594 VAh SMX120RMBP2U 8 12546 VAh SMX120RMBP2U 10 15498 VAh

Communications & Management

Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators Multi-function LCD status and control console
Emergency Power Off (EPO)	Yes
Free slots	1

Surge Protection and Filtering

Surge energy rating	645 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

GTIN	731304268529
------	--------------

Packing Units

Package 1 Length	34.21 in (86.9 cm)
Package 2 Width	39.37 in (100 cm)
Package 2 Height	44.49 in (113 cm)
Package 2 Weight	800.01 lb(US) (362.88 kg)
Package 1 Width	23.46 in (59.6 cm)
Package 1 Height	9.57 in (24.3 cm)
Package 1 Weight	100.00 lb(US) (45.36 kg)
Number of Units in Package 2	8

Unit Type of Package 2	PAL
Package 2 Length	47.24 in (120 cm)
Pallet unit layers	2
Pallet layers	4

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available
-----------------	--