

APC Essential SurgeArrest, 3 Outlets, 3 USB Charging Ports, 120V, Black

P3U3B



sales@corporatearmor.com 877.449.0458

Overview

Lead time Usually in Stock

#### Main

Mairi	
Main Input Voltage	120 V
Plug standard	NEMA 5-15P
Cable length	6 ft (1.83 m)
Provided equipment	User Manual

### **Physical**

Color	Black
Height	1.42 in (3.6 cm)
Width	5.20 in (13.2 cm)
Depth	5.20 in (13.2 cm)
Net Weight	1.08 lb(US) (0.49 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

### Input

Input power	1440 W
Input Frequency	60 Hz
Switching current capacity	12 A

### **Output**

Number of power socket outlets	3
Outlet standard	NEMA 5-15R

#### **Conformance**

<b>Product Certifications</b>	cUL Listed
Standards	UL 60950-1
Equipment protection policy	Lifetime: \$50000

### **Environmental**

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.0015240.00 m)

# **Surge Protection and Filtering**

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Surge energy rating	1080 J

# Ordering and shipping details

GTIN	731304318316
Package 1 Weight	1.17 lb(US) (0.53 kg)

## **Packing Units**

Packing Units	
Package 1 Height	2.95 in (7.5 cm)
Package 1 Width	5.39 in (13.7 cm)
Package 1 Length	6.10 in (15.5 cm)
SCC14	10731304318313
Number of Units in Package 2	10
Package 2 Weight	13.64 lb(US) (6.19 kg)
Package 2 Height	6.87 in (174.50 mm)
Package 2 Width	11.25 in (285.75 mm)
Package 2 Length	15.75 in (400.05 mm)
Number of Units in Package 3	80

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

## **Contractual warranty**

Warranty

Limited Lifetime