

# Product data sheet

Specifications



## APC Power-Saving Timer Essential SurgeArrest, 4 Outlet Wall Tap, 120V

P4GC

Product availability : Stock - Normally stocked in distribution facility



**Corporate Armor**

sales@corporatearmor.com  
877.449.0458

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage 120 V

Input Connection Type NEMA 5-15P

Provided equipment User Manual

### Physical

Color White

Height 6.50 in (16.5 cm)

Width 3.70 in (9.4 cm)

Depth 2.01 in (5.1 cm)

Net Weight 0.55 lb(US) (0.25 kg)

Mounting preference No preference

Mounting Mode Not rack-mountable

### Input

Input Frequency 50/60 Hz

Maximum Input Current per Phase 15 A

### Output

Number of power socket outlets 4

Outlet standard NEMA 5-15R

### Conformance

UL 1449 TVSS Rating 400

Product Certifications ETL

Standards UL 1449

Equipment protection policy Lifetime : \$50000

## Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	23...113 °F (-5...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	72 kA common mode
Surge energy rating	1080 J

## Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304269267
Number of Units in Package 1	1
Package 1 Weight	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	PH

## Packing Units

Package 1 Height	9.65 in (24.5 cm)
Package 1 Width	8.90 in (22.6 cm)
Package 1 Length	2.64 in (6.7 cm)
SCC14	10731304269264
Number of Units in Package 2	6
Package 2 Weight	7.88 lb(US) (3.57 kg)
Package 2 Height	11.68 in (296.67 mm)
Package 2 Width	12.13 in (308.10 mm)
Package 2 Length	19.85 in (504.19 mm)
Number of Units in Package 3	288

## Contractual warranty

Warranty	Limited Lifetime
----------	------------------