

Product data sheet

Specifications



APC Essential SurgeArrest 6 Outlet 15 Foot Cord 120V

PE615



Corporate Armor

sales@corporatearmor.com
877.449.0458

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	15 ft (4.57 m)
Number of cables	1
Provided equipment	User Manual

Physical

Color	Black Gray
Height	11.02 in (28 cm)
Width	2.05 in (5.2 cm)
Depth	1.18 in (3 cm)
Net Weight	2.01 lb(US) (0.91 kg)
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Maximum Input Current per Phase	15 A
Switching current capacity	15 A

Output

Number of power socket outlets	6
Outlet standard	NEMA 5-15R

Conformance

UL 1449 TVSS Rating	500
Product Certifications	MET Canada MET USA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$50000

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	48 kA common mode 24 kA normal mode
Surge energy rating	1080 J

Ordering and shipping details

GTIN	731304337010
Package 1 Weight	2.20 lb(US) (1 kg)

Packing Units

Package 1 Height	12.20 in (31 cm)
Package 1 Width	6.89 in (17.5 cm)
Package 1 Length	1.57 in (4 cm)
SCC14	10731304337017
Number of Units in Package 2	6
Package 2 Weight	14.13 lb(US) (6.41 kg)
Package 2 Height	13.58 in (344.93 mm)
Package 2 Width	7.6 in (193.04 mm)
Package 2 Length	10.71 in (272.03 mm)
Number of Units in Package 3	204

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration

Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	Limited Lifetime
-----------------	------------------