

APC Essential SurgeArrest PE66W, 6 Outlets, 6 Foot Cord, 120V, White

PE66W



sales@corporatearmor.com 877.449.0458

Uve	erv	/le	W
-----	-----	-----	---

Lead time Usually in Stock

Main

IVIAIII	
Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	6 ft (1.83 m)
Number of cables	1
Provided equipment	User Manual

Physical

Color	Green White
Height	1.18 in (3 cm)
Width	2.05 in (5.2 cm)
Depth	11.02 in (28 cm)
Net Weight	1.10 lb(US) (0.5 kg)
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Maximum Input Current per Phase	15 A
Switching current capacity	15 A

Output

Number of power socket outlets	6
Outlet standard	NEMA L5-15R

Conformance

UL 1449 TVSS Rating	500
Product Certifications	MET Canada MET USA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime: \$50000

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 % non-condensing
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	Non-condensing 095 %
Storage altitude	050000 ft (0.0015240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	48 kA common mode 24 kA normal mode
Surge energy rating	1080 J

Ordering and shipping details

GTIN	731304328889
Package 1 Weight	1.28 lb(US) (0.58 kg)

Packing Units

Package 1 Height	1.57 in (4 cm)
Package 1 Width	4.53 in (11.5 cm)
Package 1 Length	12.20 in (31 cm)
SCC14	10731304328886
Number of Units in Package 2	6
Package 2 Weight	8.51 lb(US) (3.86 kg)
Package 2 Height	10 in (254.00 mm)
Package 2 Width	6 in (152.40 mm)
Package 2 Length	13 in (330.20 mm)
Number of Units in Package 3	432

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration

Compliant EU RoHS Declaration
EU RONS Declaration
Yes
Yes
Yes
Product Environmental Profile
End of Life Information

Contractual warranty

Warranty Limited Lifetime