

APC Essential SurgeArrest PE76, 7 Outlets, 6 Foot Cord, 120V

PE76



sales@corporatearmor.com 877.449.0458

Overvie	V	١	١
---------	---	---	---

Usually in Stock

Main

IVIAIII	
Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	6 ft (1.83 m)
Number of cables	1
Provided equipment	User Manual

Physical

Color	Black Gray
Height	1.18 in (3 cm)
Width	2.05 in (5.2 cm)
Depth	13.70 in (34.8 cm)
Net Weight	1.21 lb(US) (0.55 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Maximum Input Current per Phase	15 A
Switching current capacity	15 A

Output

Number of power socket outlets	7
Outlet standard	NEMA 5-15R

Conformance

Product Certifications	MET Canada MET USA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime: \$50000

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 % non-condensing
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	Non-condensing 095 %
Storage altitude	050000 ft (0.0015240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	56 kA common mode 28 kA normal mode
Surge energy rating	1440 J

Ordering and shipping details

GTIN	731304328957
Package 1 Weight	1.43 lb(US) (0.65 kg)

Packing Units

I acking Office	
Package 1 Height	1.57 in (4 cm)
Package 1 Width	4.53 in (11.5 cm)
Package 1 Length	14.96 in (38 cm)
SCC14	10731304328954
Number of Units in Package 2	6
Package 2 Weight	9.48 lb(US) (4.30 kg)
Package 2 Height	10 in (254.00 mm)
Package 2 Width	6 in (152.40 mm)
Package 2 Length	16 in (406.40 mm)
Number of Units in Package 3	360

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant

EU RoHS Declaration

Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty Limited Lifetime