

Product data sheet

Specifications



APC Essential SurgeArrest 7 Outlet 6 Foot Cord 120V, White and Grey

PE76WG



Corporate Armor

sales@corporatearmor.com
877.449.0458

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	6 ft (1.83 m)
Number of cables	1
Provided equipment	User Manual

Physical

Color	Gray White
Height	1.18 in (3 cm)
Width	2.05 in (5.2 cm)
Depth	13.70 in (34.8 cm)
Net Weight	1.21 lb(US) (0.55 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Maximum Input Current per Phase	15 A
Switching current capacity	15 A

Output

Number of power socket outlets	7
Outlet standard	NEMA 5-15R

Conformance

Product Certifications	MET Canada MET USA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$50000

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	48 kA common mode 28 kA normal mode
Surge energy rating	1440 J

Ordering and shipping details

GTIN	731304343769
Package 1 Weight	1.43 lb(US) (0.65 kg)

Packing Units

Package 1 Height	1.57 in (4 cm)
Package 1 Width	4.53 in (11.5 cm)
Package 1 Length	14.96 in (38 cm)
SCC14	10731304343766
Number of Units in Package 2	6
Package 2 Weight	9.48 lb(US) (4.30 kg)
Package 2 Height	10 in (254.00 mm)
Package 2 Width	6 in (152.40 mm)
Package 2 Length	16 in (406.40 mm)
Number of Units in Package 3	360

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	Limited Lifetime
-----------------	------------------