Product data sheet

Specifications



(!) Discontinued

APC Notebook Surge Protector for AC, phone and network lines, 2 pin connection, 100-240V

PNOTEPROC8

Discontinued on: 15 June 2022

PNOTEPROC8 has not been replaced. Please contact your customer care center for more information.



sales@corporatearmor.com 877.449.0458

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Input Connection Type	IEC 60320 C8
Number of cables	1
Provided equipment	2 x 1.8 Meter Tel cable 30 cm Network patch cable Cord management straps User Manual

Physical

Color	Silver
Height	1.06 in (2.7 cm)
Width	1.26 in (3.2 cm)
Depth	3.86 in (9.8 cm)
Net Weight	0.22 lb(US) (0.1 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Input power	300 W
Maximum Line Current per phase	4 A
Input Frequency	50/60 Hz

Output

Number of power socket outlets

IEC 60320 C8 **Outlet standard**

Conformance

UL 1449 TVSS Rating	700
Product Certifications	CSA NOM UL Listed
Standards	FCC part 68
Equipment protection policy	Lifetime : \$75000

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	095 %
Storage altitude	030000 ft (0.009144.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	0 dB
Peak current	0 kA common mode 6.5 kA normal mode
Surge energy rating	180 J
Data line protection	RJ11 Modem/Fax protection (two wire single line) RJ45 10/100 Base-T Ethernet protection

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304220725
Returnability	No

Packing Units

SCC14 10731304220722

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty Limited Lifetime