

Product data sheet

Specifications



APC Home Office SurgeArrest 12 Outlets, 120V

PH12



Corporate Armor

sales@corporatearmor.com
877.449.0458

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	6 ft (1.83 m)
Number of cables	1
Provided equipment	User Manual

Physical

Color	Black
Height	1.18 in (3 cm)
Width	3.03 in (7.7 cm)
Depth	12.09 in (30.7 cm)
Net Weight	1.48 lb(US) (0.67 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Maximum Input Current per Phase	15 A
Switching current capacity	15 A

Output

Number of power socket outlets	12
Outlet standard	NEMA 5-15R

Conformance

Product Certifications	MET USA
------------------------	---------

Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	56 kA common mode 28 kA normal mode
Surge energy rating	2160 J

Ordering and shipping details

GTIN	8411314066804
Package 1 Weight	1.70 lb(US) (0.77 kg)

Packing Units

Package 1 Height	1.89 in (4.8 cm)
Package 1 Width	5.71 in (14.5 cm)
Package 1 Length	13.19 in (33.5 cm)
SCC14	10731304335945
Number of Units in Package 2	6
Package 2 Weight	11.04 lb(US) (5.01 kg)
Package 2 Height	12.6 in (320.04 mm)
Package 2 Width	6.3 in (160.02 mm)
Package 2 Length	13.78 in (350.01 mm)
Number of Units in Package 3	324

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	Lifetime
-----------------	----------