

Product data sheet

Specifications



APC Home Office SurgeArrest 12 Outlets, 120V White

PH12W



Corporate Armor
sales@corporatearmor.com
877.449.0458

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	6 ft (1.83 m)
Number of cables	1
Provided equipment	User Manual

Physical

Color	White
Height	1.18 in (3 cm)
Width	3.03 in (7.7 cm)
Depth	12.09 in (30.7 cm)
Net Weight	1.48 lb(US) (0.67 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Maximum Input Current per Phase	15 A
Switching current capacity	15 A

Output

Number of power socket outlets	12
Outlet standard	NEMA 5-15R

Conformance

Product Certifications	MET Canada
------------------------	------------

	MET USA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$150000
Environmental	
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)
Surge Protection and Filtering	
NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	56 kA common mode 28 kA normal mode
Surge energy rating	2160 J
Ordering and shipping details	
GTIN	731304336235
Package 1 Weight	1.70 lb(US) (0.77 kg)
Packing Units	
Package 1 Height	1.89 in (4.8 cm)
Package 1 Width	5.71 in (14.5 cm)
Package 1 Length	13.19 in (33.5 cm)
SCC14	10731304336232
Number of Units in Package 2	6
Package 2 Weight	11.04 lb(US) (5.01 kg)
Package 2 Height	12.6 in (320.04 mm)
Package 2 Width	6.3 in (160.02 mm)
Package 2 Length	13.78 in (350.01 mm)
Number of Units in Package 3	324
Offer Sustainability	
Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	Limited Lifetime
----------	------------------