

Product data sheet

Specifications



APC Performance SurgeArrest 11 Outlet with Phone (Splitter), Coax and Ethernet Protection, 120V

P11VNT3



Corporate Armor

sales@corporatearmor.com
877.449.0458

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	8 ft (2.44 m)
Number of cables	1
Provided equipment	6ft Network cable Coaxial cable Cord management straps Telephone Cable User Manual

Physical

Color	Black
Height	1.57 in (4 cm)
Width	4.69 in (11.9 cm)
Depth	11.89 in (30.2 cm)
Net Weight	2.34 lb(US) (1.06 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Frequency	50/60 Hz
Switching current capacity	15 A

Output

Number of power socket outlets	11
Outlet standard	NEMA 5-15R

Conformance

UL 1449 TVSS Rating	L-N: 400 L-G: 500 N-G: 500
---------------------	----------------------------------

Product Certifications	CSA NOM
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$100000

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	0 ns common mode
Common mode rejection	70 dB
Surge energy rating	3020 J
Data line protection	Analog phone line for phone/fax/modem/DSL (RJ11 connector) Network line - 10/100 Base-T Ethernet (RJ45 connector) Coaxial cable for CATV/SATV/modem/Audio-Video (coax connector)

Ordering and shipping details

GTIN	731304249023
Package 1 Weight	2.98 lb(US) (1.35 kg)

Packing Units

Package 1 Height	2.36 in (6 cm)
Package 1 Width	7.56 in (19.2 cm)
Package 1 Length	13.58 in (34.5 cm)
SCC14	10731304249020
Number of Units in Package 2	6
Package 2 Weight	19.58 lb(US) (8.88 kg)
Package 2 Height	15 in (381.00 mm)
Package 2 Width	8 in (203.20 mm)
Package 2 Length	15 in (381.00 mm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty

Limited Lifetime