# **Product data sheet**

**Corporate Armor** 

sales@corporatearmor.com 877.449.0458

Specifications





# APC SYMMETRA LX FLAME RETARDANT BATTERY MODULE

SYBT5FR

V	ve	ver	vervi	vervie	verviev

Presentation	Extended run power protection for servers, networks, and telecommunications
Lead time	Usually in Stock

### Main

Number of rack unit	0U
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide

## **Physical**

Height	5.51 in (14 cm)
Width	8.27 in (21 cm)
Depth	21.50 in (54.6 cm)
Net Weight	64.15 lb(US) (29.1 kg)
Mounting Mode	Not rack-mountable

#### Conformance

Product Certifications	CSA
Standards	UL 1778

#### **Environmental**

Ambient Air Temperature for Operation	32104 °F (040 °C)
Operating altitude	010000 ft
Relative Humidity	095 %
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage altitude	015000 ft (0.004572.00 m)
Storage Relative Humidity	095 %

## **Batteries & Runtime**

**Battery Placement** Internal Battery

Battery blocks per string	10
Battery Slots Empty	0
Included Battery Modules	0
Battery manufacturer	Yuasa
Device mounting	Enclosed battery cartridge
Battery Voltage	120 V
RBC Quantity	1

## Ordering and shipping details

**GTIN** 731304221623

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.16 in (38.5 cm)
Package 1 Width	29.53 in (75 cm)
Package 1 Length	11.26 in (28.6 cm)
Package 1 Weight	71.17 lb(US) (32.28 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
REACh Regulation	REACh Declaration		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Take-back	Take-back program available		

## **Contractual warranty**

Warranty 2 years repair or replace

## Recommended replacement(s)