

Product data sheet

Specifications



APC Smart-UPS X, Line Interactive, 750VA, Rack/tower convertible 2U, 120V, 8x 5-15R NEMA, SmartConnect port, Extended runtime, TAA

SMX750CUS



Corporate Armor

sales@corporatearmor.com
877.449.0458

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Input Connection Type	NEMA 5-15P
Output connection type	8 NEMA 5-15R
Provided equipment	CD with software

Physical

Color	Black
-------	-------

Input

Efficiency at full load	75...154 V adjustable
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
----------------------------------	---------------------------------

Conformance

Product Certifications	ENERGY STAR V2.0 (USA)
------------------------	------------------------

Environmental

Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Batteries & Runtime

Battery power in VAh	269 VAh runtime
Battery Charge Power (Watts)	104 W rated
Battery option	SMX48RMBP2U 5 939 VAh

Ordering and shipping details

GTIN	731304424475
------	--------------

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Offer Sustainability

EU RoHS Directive Under investigation

WEEE The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty 3 Years