CyberPower

RB1270X2D REPLACEMENT BATTERIES

Restore life to UPS systems that have weak or depleted internal batteries

The RB1270X2D UPS Replacement Battery Cartridge restores life to CyberPower UPS systems that have weak or completely depleted internal batteries. The RB1270X2D contains two 12V/7Ah batteries, certified to meet or exceed original manufacturer specifications. This leak-proof, sealed lead-acid battery never requires replacement fluid. The pre-assembled cartridge installs easily into your CyberPower UPS system and is shipped with reusable packaging for delivering expired batteries to a suitable recycling center. The RB1270X2D comes with instructions, recycling information, and an eighteen-month warranty.



• OR750PFCLCD

FEATURES

- Number of batteries: 2
- Battery size: 12V/7Ah
- Battery type: Sealed lead-acid
- Dimensions WxHxD (in.): 5.1 x 4.1 x 5.9
- Weight (lbs.): 9.5
- OEM certified: Yes
- Leak-proof casing: Yes
- User replaceable: Yes
- Warranty: 18-Month





sales@corporatearmor.com 877.449.0458

Cyber **Power**

standards and is certained not use that Upder to the province in NONSPILLABLE, sealed, lead-acid battery

SPECIFICATIONS

BATTERY	
Battery Quantity	2
Battery Size	12 V / 7 Ah
Battery Type	Sealed Lead-Acid Battery
User-Replaceable Battery	Yes
PHYSICAL DIMENSIONS	
Physical Dimensions - WxHxD (cm)	12.95 x 10.41 x 14.99 cm
Physical Dimensions - WxHxD (mm)	130 x 104 x 150 mm
Physical Dimensions - WxHxD (in.)	5.1 x 4.1 x 5.9 in.
Weight (kg)	4.31 kg
Weight (lb)	9.50 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - WxHxD (cm)	18.54 x 16.0 x 20.57 cm
Shipping Dimensions - WxHxD (mm)	185.42 x 160.02 x 205.74 mm
Shipping Dimensions - WxHxD (in)	7.3 x 6.3 x 8.1 in.
Weight (kg)	4.54 kg
Weight (lb)	10.0 lbs.
ENVIRONMENTAL	
Operating Relative Humidity	0 - 90% (non-condensing)
Operating Temperature	32 - 104°F (0 - 40°C)
COMPATIBILITY	
UPS Models	OR750PFCLCD
WARRANTY	